

MODELO DE CALDERA		100	200	300	400	500	600	800	1.000	1.300	1.500	1.800	2.000	2.500	3.000	
Producción normal	Kg/h	100	200	300	400	500	600	800	1.000	1.300	1.500	1.800	2.000	2.500	3.000	
Potencia térmica	Th/h	60	120	180	240	293	351	465	581	753	869	1.041	1.157	1.445	1.720	
	Kw	70	140	210	280	340	408	540	675	875	1.010	1.210	1.345	1.680	2.000	
Rendimiento	%	90														
Consumo Combustible	Gas Natural	Nm ³ /h	7	14	22	29	35	42	55	69	90	104	124	138	173	205
	Fuel - Oil	Kg/h	----	----	----	----	----	----	----	67	87	100	120	134	167	199
	Gasoleo	l/h	7	14	22	29	35	42	55	69	90	104	124	138	173	205
Sobrepresión hogar	mm.c.a.	15	15	18	18	20	25	25	30	32	35	37	45	48	50	
Peso Transporte	Kg.	900	1.100	1.520	1.550	1.920	1.950	2.660	2.700	3.515	3.575	4.225	4.285	5.340	6.175	
Max. Presión Categoría I	Bar	16						13			10		7,5		5,5	5
Dimensiones	mm.	A	1.385	1.545	1.970	1.970	2.220	2.220	2.717	2.717	3.109	3.109	3.522	3.522	3.732	4.100
		B	1.200	1.325	1.470	1.470	1.550	1.550	1.746	1.746	1.900	1.900	1.906	1.906	2.325	2.100
		C	1.220	1.350	1.490	1.490	1.570	1.570	1.805	1.805	1.950	1.950	2.037	2.037	2.278	2.306
		D	1.190	1.350	1.785	1.785	2.030	2.030	2.536	2.536	2.915	2.915	3.328	3.328	3.538	3.904
		E	900	1.025	1.170	1.170	1.250	1.250	1.746	1.746	1.620	1.620	1.647	1.647	1.874	1.942
		F	700	800	900	900	950	950	1.150	1.150	1.380	1.380	1.431	1.431	1.510	1.680